

FB-2513

UV Flatbed Printing Machine



Machine configuration depending on different model. For more information, please call local dealer.

PRODUCT INTRODUCTION



The machine comes standard with 4 rows of Ricoh industrial print head



Breakthrough AI algorithm, capable of identifying and aligning inkjet printing with just one click completion



The precision can reach 0.1 millimeters



Ink can be equipped with either a light oil scheme or a fluorescent scheme

FB-2513

UV Flatbed Printing Machine

FORNI

► Specifications

Machine configuration are different between models, Please consult your local distributor for more information

Items		Technical Parameters
Model		FB-2513
Print head	Print type	Ricoh industrial print head
	QTY	3-12Pcs
Ink	Color	C/M/Y/K/+W/+V Support optional light oil solution
	Ink type	UV ink
	Ink supply	Pump ink supply
Speed	Production mode	14-42 m ² /h White/Color Mode
	Quality mode	12-36 m ² /h White/Color Mode
	Draft mode	11-32 m ² /h White/Color Mode
Media	Photo mode	2400mm × 1240mm
	Media type	Acrylic, ceramic tiles, glass, aluminum, wooden doors, PVC sheet, carpet and other printed materials
	Media transfer	Motor automatic feeding and taking up system
Cleaning		Positive pressure cleaning device
Interface		USB
Working Environment		Temperature: 18°C-30°C, Humidity : 30%-80%
Power Supply	Frequency: 50HZ/60HZ Power : Maximum 7500W	
	Rated voltage: AC220V (±10%)	
Machine Dimension		L4900 × W2050 × H1460 (mm)
Machine Weight		1650Kg

Print speed varies over the computer, the media will have errors of different width to the actual subject.

Nanjing Meiyin Digital Technology Co., Ltd

Address: Building B, No. 8 Pengcheng Road, Jiangning District,

Nanjing City, Jiangsu Province, China

www.fornidigital.com

admin@fornidigital.com